

DK301 快速接頭 (美規) DK301 QUICK COUPLER

產品	圖片	型號	管接尺寸	牙徑	總長尺寸(mm)
快速接頭 (母)		DK301-3	3/8"軟管		
		DK301-4	1/2"軟管		
		DK301-3H	3/8"鐵氟龍管		
		DK301-4H	1/2"鐵氟龍管		
		DK301-C3H	3/8"鐵氟龍管		
		DK301-C4H	1/2"鐵氟龍管		
		DK301-L3	3/8"軟管		
		DK301-L4	1/2"軟管		
公接頭- 標準長度		DB3-1T		1/8PT	
		DB3-2T		1/4PT	
		DB3-3T		3/8PT	
		DB3-4T		1/2PT	
公接頭- 加長長度		DB3-1T		1/8PT	*50/75/100/125/150/175 /200
		DB3-2T		1/4PT	
		DB3-3T		3/8PT	
公接頭-L型		DB3-1T-L		1/8PT	
		DB3-2T-L		1/4PT	
		DB3-3T-L		3/8PT	

*型號採購原則如下：如需1/4 PT牙徑，總長100mm，型號為：DB3-2T-100如需其他長度尺寸，歡迎諮詢訂製

適用流體Application: 空氣、油、水(Gas, Water, Oil)
工作壓力Working pressure: Max. 8 kg/cm²
工作溫度Working Temp.: 0~180℃

