




型號 ITEM NO.	E (長度) LENGTH (mm)	N (外徑) O.D. (mm)	SW	H(管接尺寸) TUBE SIZE	材質 MATERIAL
GK501-3	73	28	21H	3/8" 塑膠軟管 (Hose)	銅 BRASS
GK501-4	73			1/2" 塑膠軟管 (Hose)	
GK501-3TA	62			3/8"PT 內牙 (Female thread)	
GK501-3TB	64			3/8"PT 外牙 (Male thread)	
GK501-S2	68			φ 8 x φ 12 PU 管 (PU tube)	
GK501-M	68			3/8"x 1/2" PU 管 (PU tube)	
GK501-3H	65			3/8" (喇叭)白鐵紗管 9/16-18 37°flared	
GK501-4H	69			1/2" (喇叭)白鐵紗管 3/4-16UNF 37°flared	
適用流體 Application	空氣、水、油 Gas、Water、Oil	工作壓力 Working Pressure Max. 10 kg/cm ²		工作溫度 Working Temp. 0~80℃ or 0~180℃	
 單閉式 Single shut-off		 直通式 Non-valved		Above item No. are single shut-off type , please add – OH after item No. if Non-valved type required 。 EX. : GK501-M-OH	

GK501型快速接頭專用模具插心

MALE PLUG FOR GK501 TYPE

全新自動上鎖快速接頭NK401型 & GK501型使用說明
Auto-lock QRC NK401 & GK501 instruction

- ① 接合時，請直接將插心推入快速接頭，其結構會將插心與快速頭自動上鎖，防止脫落。
CONNECTION: Please push plug into socket directly, the special design will lock plug and socket automatically.
- ② 分離時，請按步驟 1. 將外殼順時針旋轉至固定位置。
2. 往前推，即可分離。
DISCONNECTION: 1. Please turn the sleeve clockwise.
2. Then push forward.



型號 ITEM NO.	E 1(長度) LENGTH (mm)	D(管接尺寸) TUBE & THREAD	SW	材質 MATERIAL
GB	45	1/4"PT	16H	銅 BRASS
	45	3/8"PT	17H	
	47	1/2"PT	21H	
GL	37	1/4"PT、3/8"PT	18□	
	38	1/2"PT	22□	
GX	51.5	3/8"、1/2" 塑膠軟管(HOSE)		
GS2	50	φ 8 x φ 12 PU 管 (PU tube)	17H	
GM	50	3/8"x 1/2" PU 管 (PU tube)		
GLR	46.5	1/4"PT、3/8"PT	22□	
★ GLR 為 90° L 型旋轉插心，其結構可 360° 旋轉。 ★ GLR is a 90° L rotate type plug, the structure is allowed to 360° rotation.				N: φ 12.0

